

TECHNICAL INFORMATION



\$1P EN ISO 20345: 2011 S1P SRC CI HI









PARADE
















wave dissipation

Scuff-resistant Extra-flexible shield sole



7824 BLACK | 35▶48

- SHIELD ONE ABRASION PROTECTION
- FABRIC + PU RESISTANT TO 16,000 **ABRASION CYCLES**
- BE-FLEX FLEXIBLE SOLE



COMPOSITION

Upper	Shield one
Front reinforcement	TPU
Lining	3D mesh
Тое сар	Composite
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Fabric
Sole	Two-density polyurethane
Weight size 42*	535 g * Weight per shoe

**	Coefficient obtained size 42	flat		heel	
		Standard	Parade	Standard	Parade
	SRA Ceramic floor/Nals (soap solution)	0,32	0,49	0,28	0,54
	SRB Steel/Glycerine (oil)	0.18	0.18	0.13	0.15

SAFFTY TABLE

JAI	LII IADLL
S	Toe protection (safety toe cap)
P	Puncture-resistance
SRC	Slip-resistance**
E	Energy-absorbing heel
A	Anti-static
FO	Hydrocarbon-resistant
CI	Sole insulation (cold)
H	Sole insulation (heat)
	Non-magnetic




TECHNICAL INFORMATION

NVIRONMENTAL **FEATURES**

At Parade, we carry out a life cycle analysis to measure the environmental impact of each of our models: from the extraction of raw materials, manufacturing, use, logistics, right through to the end of the product's life. Our environmental impact calculators, developed in-house using ADEME's EMPREINTE® database, have been certified by AFNOR for textiles and validated by the Pôle Eco-conception* for footwear.

* The Pôle Eco-conception is the French national centre for eco-design and life-cycle performance. Its expertise is recognised nationally and internationally by ADEME, the French Ministry of the Environment, AFNOR, ISO and the UN-environment



RAW MATERIALS

60%

Raw materials: contribution to the carbon footprint as a %

MANUFACTURING

22 %

Manufacturing: contribution to the carbon footprint as a %

TRANSPORT

7 %

Transport: contribution to the carbon footprint as a %

DISTRIBUTION

Distribution: contribution to the carbon footprint as a %

Use: contribution to the carbon footprint as a % **END OF LIFE**

End-of-life: contribution to the carbon footprint as a %



RAW MATERIALS

99 %

Raw materials: contribution to water pollution as a % MANUFACTURING

Manufacturing: contribution to water pollution as a %

TRANSPORT

0%

Transport: contribution to water pollution as a %

DISTRIBUTION

0%

Distribution: contribution to water pollution as a %

Use: contribution to water pollution as a %

END OF LIFE

1 %

End of life: contribution to water pollution as a %

Packaging containing at least 70% recycled materials



Stitching country: China / Assembly country: China / Finishing country: China





- DRS SYSTEM 2 technology for shock wave dissipation
- BE-FLEX 2.0 technology for a flexible sole and maximum comfort
- VPS SYSTEM technology: supports the arch of the foot
- Exclusive SHIELD-ONE material: fabric + ultra-resistant PU (meets abrasion-resistance requirements imposed by the EN388 glove standard - performance level 4/4)
- Ultra-breathable 3D MESH

^{*} Based on a size 37 for women and a size 42 for men and unisex